

IN THE CLAIMS:

The claims remain as follows:

1. (Previously Presented) A method for configuring web pages, comprising:
receiving a request for a web page comprising displayable content including user-selectable elements through which a user invokes one or more executable functions;
providing the web page with the displayable content;
parsing the web page to identify the user-selectable elements;
disabling at least portion of the user-selectable elements on the basis of a pre-defined transform definition to produce a re-configured web page, thereby making the one or more executable functions corresponding to the portion of the user-selectable elements inaccessible to the user viewing the re-configured web page without associating substituted functionality with the disabled portion of the user-selectable elements; and then
returning the re-configured web page for display.
2. (Previously Presented) The method of claim 1, wherein the portion of the user-selectable elements for which the one or more executable functions are made inaccessible remain visible while the one or more executable functions are inaccessible.
3. (Original) The method of claim 1, wherein disabling comprises removing the portion of the user-selectable elements from the web page prior to returning the re-configured web page.
4. (Previously Presented) The method of claim 2, wherein the pre-defined transform definition is an XSL transform defined for the web page and specifying the portion of the user-selectable elements to be disabled.
5. (Original) The method of claim 1, wherein the user-selectable elements are graphical user interface elements.

6. (Original) The method of claim 1, wherein the request is issued by a web browser.

7-10. (Canceled)

11. (Previously Presented) A computer readable storage medium containing a program which, when executed, performs an operation for configuring web pages, the operation comprising:

receiving a request for a web page comprising displayable content including user-selectable elements through which a user invokes one or more executable functions;

providing the web page with the displayable content;

parsing the web page to identify the user-selectable elements;

disabling at least portion of the user-selectable elements on the basis of a pre-defined transform definition to produce a re-configured web page, thereby making the one or more executable functions corresponding to the portion of the user-selectable elements inaccessible to the user viewing the re-configured web page without associating substituted functionality with the disabled portion of the user-selectable elements; and then

returning the re-configured web page for display.

12. (Previously Presented) The computer readable medium of claim 11, wherein the portion of the user-selectable elements for which the one or more executable functions are made inaccessible remain visible while the one or more executable functions are inaccessible.

13. (Original) The computer readable medium of claim 11, wherein disabling comprises removing the portion of the user-selectable elements from the web page prior to returning the re-configured web page.

14. (Previously Presented) The computer readable medium of claim 12, wherein the pre-defined transform definition is an XSL transform defined for the web page and specifying the portion of the user-selectable elements to be disabled.

15. (Original) The computer readable medium of claim 11, wherein the user-selectable elements are graphical user interface elements.

16-23. (Canceled)

24. (Previously Presented) A method for configuring web pages, comprising:
receiving a request for a web page comprising displayable content including user-selectable elements through which a user invokes one or more executable functions;

providing the web page with the displayable content;

parsing the web page to identify the user-selectable elements;

disabling at least portion of the user-selectable elements on the basis of a pre-defined transform definition to produce a re-configured web page, thereby making the one or more executable functions corresponding to the portion of the user-selectable elements inaccessible to the user viewing the re-configured web page without associating substituted functionality with the disabled portion of the user-selectable elements; wherein the pre-defined transform definition is an XSL transform defined for the web page and specifying the portion of the user-selectable elements to be disabled; and then

returning the re-configured web page for display.

25. (Previously Presented) A computer readable storage medium containing a program which, when executed, performs an operation for configuring web pages, the operation comprising:

receiving a request for a web page comprising displayable content including user-selectable elements through which a user invokes one or more executable functions;

providing the web page with the displayable content;

parsing the web page to identify the user-selectable elements;

disabling at least portion of the user-selectable elements on the basis of a pre-defined transform definition to produce a re-configured web page, thereby making the one or more executable functions corresponding to the portion of the user-selectable elements inaccessible to the user viewing the re-configured web page without associating substituted functionality with the disabled portion of the user-selectable elements; wherein the pre-defined transform definition is an XSL transform defined for the web page and specifying the portion of the user-selectable elements to be disabled; and then

returning the re-configured web page for display.